

CLICKABLE CEMENT TILE (CCT)

Technical Data Sheet



by LICO

	dimensions & thickness / 尺寸和厚度	EN 427 & EN 428	ca. 920 x 460 x 7,5 mm ca. 1235 x 200 x 7,5 mm
	classification / 类别	EN 16511	Commercial 33 商用33
	total weight / 重量	EN 430	ca. 12 000 g/m ²
	impact sound reduction / 降噪性	EN ISO 717-2	ca. 19 dB
	effect of castor chair / 抗椅轮耐磨损性	EN 425	fulfil 达标
	room sound improvement / 噪声改善度	IHD-W-31	35%
	reaction of fire / 防火性能	EN ISO 9239-1	Bfl s1
	dimensional stability / 尺寸稳定性	EN 434	< 0,01 %
	thermal resistance / 隔热保温性	EN 12524	ca. 0,05 m ² K/W
	residual indentation / 压痕残余度 (抗压性)	EN 433	0,00 mm
	reaction to static electricity / 抗静电性	EN 1815	< 2,0 kV antistatic 抗静电
	lightfast / 光照色牢度	ISO 105	7 / 8
	coefficient of friction / 防滑等级	EN 51130	R 10
	resistance to chemicals / 抗化学性能	EN 423	very good resistance 非常好的抵抗力
	emissions value / 挥发性有机物质排放量		< 100 ppm
	swellness value 24h / 24小时浸泡后膨胀厚度	EN 317	0 %
	locking strenght / 装配板锁紧强度	ISO 24334	> 500 kg/lfm - kg/m
	abrasion resistance / 耐磨性	EN 14354 EN 13329	> 10 000 WR4 AC5
	micro scratch resistance / 耐刮擦性	EN 16094	MSR-A1/MSR-B1
	effect of a furniture leg / 家具腿抗刮性能	EN 424	no damage shall be visible 无可见损伤
	stain resistance / 耐污性	EN 438-2	Grad 5 / 5
	slip resistance / 防滑性能	EN 13893	Klasse DS DS类

Thickness 7.5mm



Fulfill the requirements of Green Guard Gold
符合Green Guard Gold 的要求



www.blauer-engel.de/UZ120

The details given above may be subject to change for the benefit of further improvements.

The displayed floor designs might be slightly different to the original.